

# XS-XVR6108S-4KL-2AI

DVR 5n1 X-Security

8 CH HDTVI/HDCVI/AHD/CVBS (4K)

+ 8 IP (8Mpx)

Audio over coaxial

Resolution 4K (7FPS)

2 CH facial recognition

8 CH Human and vehicle recognition



X-Security

XVR 5n1

16 CH video HDTVI/HDCVI/AHD/CVBS / 8+8 IP / 8 CH audio

H.265+/H.265/H.264+/H.264

Resolution 4K (7FPS) or 6Mpx (10FPS) or 5Mpx (12FPS) 4K-N, or 4MP/3MP (15FPS) 4M-N/1080P/720P/960H/D1/CIF or (25/30FPS) [%VAR%] [%VAR%]

PTZ Control (RS485/Coaxial)

Audio over coaxial

HDMI Full HD, VGA & CVBS Outputs

2 CH comparison of face

Human and Vehicle Recognition (Available for 8 CH coaxial video)

Mouse

2 USB Ports

Space for 1 HDD

Compact size

# Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	8 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 16 IP Channels (8Mpx), replacing all the BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Video / audio compression	H.265+/H.265/H.264+/H.264
Display resolution	HDMI: 4K, 1920×1080, 1280×1024, 1280×720 VGA: 1920×1080, 1280×1024, 1280×720
Total bandwidth	128 Mbps
Coding	All channel: 4K(1 fps–7 6MP(1 fps–10 fps); 5MP(1 fps–12 4K-N, fps); 4MP/3MP(1 fps–15 4M-N/1080P/720P/960H/D1/CIF (1 fps–25/30 [%VAR%] [%VAR%] fps); [%VAR%] [%VAR%] fps)
Dual-Stream encoding	960H (1 fps–15 fps); D1/CIF(1 fps–25/30 [%VAR%] fps)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Audio inputs	8 BNC, 1 RCA Channel
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Alarms	No
Video analysis	IVS: Tripwire   Area intrusion   Abandoned object   Face detection IP Mode, Face Recognition and IVS cannot be enabled at the same time
Facial recognition	Up to 2 analog channels for live face comparison
Intelligent motion detection	Up to 16 channels capable of classifying targets amongst humans and vehicles
Recording method	Manual, programmed, motion detection, alarm
Backup	USB / Network
Internal memory	1 SATA HDD 3.5" of up to 16 TB (not included)
Communication	RS485 (PTZ) /2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12V / 2A
Dimensions / Weight	49 (H) x 333 (W) x 315 (D) mm / 0.9 Kg