

# HWD-7104MH-G3S

5n1 Hikvision recorder

4 CH HDTVI / HDCVI / AHD / CVBS /  
4 IP

8Mpx (8FPS) / 5Mpx (12 FPS)

Compression H.265 Pro+ / H.265 Pro

Full HD HDMI and VGA Output

Audio over HDTVI Coaxial



Hikvision HiWatch Series

DVR 5n1

4 CH video HDTVI/HDCVI/AHD/CVBS / 4 IP / 4 CH audio

H.265 Pro+/H.265 Pro

Resolution per channel: 8 MP (8FPS) or 8Mpx Lite (15FPS)

Audio over coaxial cable HDTVI

PTZ Control (Coaxial)

Full HD HDMI and VGA Output

Mouse

Space for 1 HDD

# Specifications

Brand	Hikvision
Range	HiWatch Series
Video format	HDTV I / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC, (HDTV I / HDCVI / AHD / CVBS)
Hybrid configuration	4 channels BNC and 4 IP channels (up to 8Mpx)
Video outputs	1 HDMI Full HD, 1 VGA
Audio	4ch on Coaxial cable (HDTV I), 1 input / 1 output RCA
Bidirectional audio	Using Audio Inputs and RCA Output
Video / audio compression	H.265 Pro+/H.265Pro/H.265/H.264+/H.264 /G.711u
Display resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	32 Kbps at 10 Mbps
Recording resolution	8Mpx / 5 Mpx / 4Mpx / 3Mpx / 1080p / 720p / WD1 / 4CIF / VGA / CIF
Main Stream coding	8 Mpx Lite (1~15 FPS), 8Mpx (1~8 FPS) 5 Mpx (1~12 FPS) / 4 Mpx (1~15 FPS) / 3 Mpx (1~18 FPS) / 1080p / 720p / WD1 / 4CIF / VGA / CIF (1~25 FPS) * 8Mpx (1~8 FPS) only available for the channel 1
Extra Stream coding	WD1 / 4CIF / 2CIF (1~25 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
VCA	Line Crossing and Area Intrusion
Alarms	No
Recording method	Manual, programmed, motion detection
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 10TB (not included)
Communication	2 x USB 2.0 (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser, HikConnect Smartphone App and PC IVMS Software 4200
Power	DC 12 V / 1.5 A, < 10W
Dimensions / Weight	45 (H) x 260 (W) x 260 (D) mm / 1 Kg