

# DS-7108NI-Q1/8P/M(D)

Hikvision

VALUE range

NVR for IP cameras

8 CH video PoE 75 W / Max

resolution 4 Mpx

Bandwidth 60 Mbps

Supports 1 hard disk



Hikvision

Value Range

NVR for IP cameras

8 CH PoE 75 W

Supported incoming bandwidth 60 Mbps

Maximum resolution 4 Mpx

Compression H.265+/H.265/H.264+/H.264

HDMI FullHD and VGA output

IP Dual Stream Access

Mouse

Space for 1 HDD

WEB, CMS and Smartphone interface

ONVIF Compatible

# Specifications

Brand	Hikvision
Range	VALUE
Inputs for IP cameras	Switch of 8 PoE IEEE802.3af/at ports [%VAR%] (max. 75 W)
Power over Ethernet	8 (Max. 75W)
IP compatible cameras	HIKVISION (native protocol), ONVIF
Video outputs	1xHDMI FullHD, 1xVGA simultaneous
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	HDMI: 1920x1080, 1280x1024, 1280x720, 1024x768 VGA: 1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	60 Mbps downstream / 60 Mbps upstream
Stream Type	Video / Video + Audio
Main Stream recording	4MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Decoding capacity	2CH@4MPx, 4CH@1080p
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Motion Detection	Motion detection 2.0 with classification of humans and vehicles applied in motion detection Only available using cameras that also have Motion Detection 2.0.
Alarms	No
Recording method	Manual, programmed, motion detection
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Remote connections	16
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 (Rear part) / 1 x RJ45 10/100M (Ethernet)
Power	DC 48 V / 1.8 A, ? 10 W (without HDD)
Operating temperature	-10°C ~ 55°C (10%-90% Humidity)
Dimensions / Weight	48 (H) x 265 (W) x 225 (D) mm / 1 Kg (without HDD)