

WizSense 4MP outdoor IP Dome

**STARLIGHT****H.265+****P2P****Wiz Sense**

- Dahua WizSense IP Dome
- 4MP@25/30ips, Smart H.265+
- ICR, 0.008/0.0008 lux, Smart IR 30m
- 2.8mm fixed optics
- WDR 120dB, 3D-NR, 4 ROI
- Perimeter protection
- SMD Plus
- Built-in microphone
- MicroSD slot, RJ45, Onvif, IP67, 3AXIS, PoE



Reference / Model

DAHUA-4125 / DH-IPC-HDW2441TP-S-0280B-BLACK

4 megapixel 1/2.9" CMOS sensor

Compression formats: Smart H.265+, Smart H.264+, H.265, H.264, MJPEG

Digital resolution: 4MP (2688x1520), 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720), D1 (704x576), VGA (640x480), CIF (352x288)

Stream 1: 4MP (2688x1520, 1~20 ips), 4MP (2560x1440, 1~25/30 ips)

Stream 2: D1 (1~25/30 ips)

Day/Night mode with removable mechanical filter

Smart IR: 1 IR led, 30 meters

0.008 lux F1.6 (color), 0.0008 lux F1.6 (B/W), 0 lux IR on

2.8 mm fixed optics

Angle of view: 95°(H), 52°(V), 114°(D)

Imaging modes: BLC, HLC, 120dB WDR, 3D-NR, Mirror

White balance with 6 modes

WizSense 4MP outdoor IP Dome

| Reference / Model | DAHUA-4125 / DH-IPC-HDW2441TP-S-0280B-BLACK |
|---|---|
| Automatic and manual gain control | |
| Supports 4-zone videosensor, 4 regions of interest (ROI) and 4-zone privacy masking | |
| Perimeter protection with cross-line detection and intrusion detection (both modes support human/vehicle classification) | |
| SMD Plus | |
| Built-in microphone | |
| MicroSD card slot up to 256GB (not included) | |
| Network interface: RJ45 (10/100 Base-T) | |
| Network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP | |
| ONVIF (Profile S/T), CGI, P2P, Milestone, SDK and API support | |
| Up to 6 users | |
| Remote viewing via IE, Chrome, Firefox browsers | |
| DSS, DMSS management software | |
| Compatible with IOS and Android mobile devices | |
| Power supply: 12V DC / PoE (802.3af) | |
| Maximum power consumption: 4.2W (12V) / 5.1W (PoE) | |
| Storage temperature from -40°C ~ +60°C | |
| Operating temperature -40°C ~ +60°C | |
| Relative humidity: <95%. | |
| IP67 degree of protection | |
| Metal and plastic housing | |
| Dimensions: Ø109.9 x 100.9 (H) mm | |
| Weight: 370 g | |
| 3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation) | |