

Starlight 16X 2MP Outdoor PTZ Dome



- Dahua StarLight 4-in-1 PTZ dome
- 2MP@25/30ips
- ICR, 0.005/0.0005 lux
- Switchable 4 in 1 output
- 16X optical zoom: 5~80mm
- WDR 120dB, 2D/3D-NR
- 300 presets DH-SD, Pelco-D/P
- 1 audio input
- 2 alarm inputs / 1 alarm output
- RS485
- IP66, IK10
- 12V DC
- Power supply included.



Reference / Model	DAHUA-4375 / DH-SD42216DB-HC
1/2.8" Sony® STARVIS™ 2 megapixels CMOS	
Digital resolution: 1080P (1920x1080), 720P (1280x720), D1 (704x576; 704x480)	
Frames per second: 25/30 fps @1080P, 25/30/50/60 fps @720P	
4-in-1 video output: HDCVI/HDTVI/AHD/CVBS (CVBS used for debugging only)	
0.005 lux F1.6 (color) / 0.0005 lux F1.6 (B/W)	
Removable mechanical filter	
16X optical zoom: 5 ~ 80 mm	
Angle of view: 59.6°~5.4°(H), 34.6°~3°(V), 67.3°~6.2°(D)	
Auto, semi-automatic and manual focus control	
Auto and manual iris control	
16X digital zoom	
Image modes: BLC, HLC, WDR 120dB, 2D/3D-NR, digital Defog	
White balance with 8 modes	

## Starlight 16X 2MP Outdoor PTZ Dome

Reference / Model	DAHUA-4375 / DH-SD42216DB-HC
Automatic and manual gain control	
Privacy masks	
Horizontal Positioner: 0° ~ 360° continuous	
Vertical positioner: 0° ~ +90°, autoflip 180°, manual speed: 0.1° ~ +90°, autoflip 180°.	
Manual speed: 0.1° ~ 300°/sec (H), 0.1° ~ 200°/sec (V)	
Preset speed: 300°/sec. (H), 200°/sec. (V)	
300 presets	
DH-SD and Pelco-D/P protocols (automatic recognition)	
5 patterns, 8 rounds of up to 32 presets each, 5 scans	
RS485 port (1200 ~ 9600 bps)	
1 audio input	
2 alarm inputs / 1 alarm output	
Power supply: 12V DC, 3A (±10%)	
Power consumption: 8W (12W with PTZ active)	
Operating temperature from -30°C ~ +60°C	
Relative humidity: ≤951%.	
Degree of protection IP66	
Vandal-proof IK10	
Lightning-proof 6KV	
Dimensions: Ø170,4 x 154,9 mm	
Net weight: 1.8 kg	
Gross weight: 3.3 kg	
Power supply included	