

DAHUA-4078

DH-HAC-HDW1500TP-IL-A-0280B-S2



4 in 1 5MP outdoor dome



- Dahua 4 in 1 dome
- 5MP@25/30fps (CVI)
- Switchable 4 in 1 output
- ICR, 0.05/0.005 lux, Smart Dual Light 40m
- Fixed optics 2.8 mm
- Digital WDR
- Built-in microphone
- IP67 protection, 3AXIS



Reference / Model

DAHUA-4078 / DH-HAC-HDW1500TP-IL-A-0280B-S2

5 megapixel CMOS sensor

Digital resolution: 5MP (2880x1620), 4MP (2560x1440), 1080P (1920x1080), 960H (960x756)

Frames per second: 25/30 fps @5MP (CVI), 25/30 fps @4MP (CVI/TVI/AHD), 25/30 fps @1080P (CVI)

Switchable 4-in-1 output

Day/night mode with removable mechanical filter

0.05 lux F1.6 (color) / 0.005 lux F1.6 (B/W) / 0 lux IR On

Smart Dual Light: 2 IR leds + 2 white light leds, 40 meters

2.8 mm fixed optics

Angle of view: 106°(H), 56°(V), 125°(D)

Imaging modes: BLC, HLC, Digital WDR, 2D-NR, Mirror

Illumination modes: Smart IR + Smart Light / Smart IR / Smart Light

Auto white balance

Automatic and manual gain control

DAHUA-4078

DH-HAC-HDW1500TP-IL-A-0280B-S2



4 in 1 5MP outdoor dome

Reference / Model	DAHUA-4078 / DH-HAC-HDW1500TP-IL-A-0280B-S2
	Supports 8-zone privacy mask
	Built-in microphone
	Power supply: 12V DC ($\pm 30\%$)
	Power consumption: 4.5W (max.)
	Storage temperature: $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$)
	Operating temperature: $-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$ ($-40^{\circ}\text{C} \sim +60^{\circ}\text{C}$)
	Relative humidity: $<95\%$ (non-condensing)
	IP67 degree of protection
	Metal housing
	Dimensions: $\varnothing 106 \times 93.6 \text{ mm}$
	Gross weight: 600 g
	Net weight: 470 g
	3AXIS: $0^{\circ} \sim 360^{\circ}$ (PAN), $0^{\circ} \sim 78^{\circ}$ (TILT), $0^{\circ} \sim 360^{\circ}$ (Rotation)