

SF-IPB380A-8I2

Safire Smart

Bullet IP camera range I2 AI

Advanced

Resolution 8 Megapixel (3840x2160)

Lens 2.8 mm | Audio | IR 50m

Advanced AI: Video Metadata and

Facial Detection

Waterproofing IP67 | PoE

(IEEE802.3af)



Safire Smart

Range I2 with Advanced Artificial Intelligence

Bullet IP camera

1/2.8" Progressive Scan CMOS

8 Megapixel (3840x2160)

2.8 mm Lens

0 Lux

IR Range 50 m

Compression H.265+ / H.264+

WDR

3DNR

Audio

Advanced Artificial Intelligence: human, vehicle and non-motorized vehicle detection

Facial Capture

Video metadata

Human, vehicle and non-motorized vehicle counts

WEB, CMS, Smartphone and NVR interface

MicroSD card up to 256GB

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	I2
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840x2160)
Minimum illumination	Colour: 0.02 Lux @(F1.6, AGC ON), 0 Lux with IR
IR range	50 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	25 FPS (8Mpx, 6Mpx, 5Mpx, 4Mpx, 2K, 3Mpx, 1080P, 720P) HFR mode: 60 FPS (1080P / 720P)
Extra Stream rate	25 FPS (720P, D1, CIF, VGA, 480x240)
Third Stream Rate	25 FPS (720P, D1, 480x240, CIF)
Compression	H.265+ / H.265 / H.264+ / H.264
Bitrate	64 Kbps ~ 12Mbps
Lens	2.8 mm
Field Of View (FOV)	H: 104°, V: 55°, D: 125°
Range performance	83 m (D), 33 m (O), 17 m (R), 8 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Smart Features	Advanced Artificial Intelligence: Classification of human, vehicle and non-motorized vehicle over: Area Intrusion, Line Crossing, Entry Region, Exit Region
	Face Detection and Face Capture
	Counting of people, vehicles and non-motorized vehicles
	Video Metadata (Feature Extraction): - Human: up to 13 characteristics (color of clothing, hat, backpack, ...) - Vehicle: up to 5 characteristics (color, type, brand, model and address) - Non-motorized vehicle: Up to 1 characteristics
Audio	Other smart events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
	1 Input
	G711A / U
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
EIS (Electronic Image Stabilizer)	Yes
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 702 mA / 9W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	80.30 (H) x 80.50 (W) x 217.80 (D) mm
Weight	680 g