

SF-D040-5E1

Safire Smart

Dome camera 4 in 1 Range E1

5 Mpx (2560x1936), 1/2.7" CMOS

2.8 mm Lens | 30 m IR range

DWDR, HLC, BLC, AGC

Waterproof IP67, Anti-vandal IK10



Safire Smart

E1 Professional range of high quality and performance

HDTVI, HDCVI, AHD and Analog Dome Camera

CMOS 1/2.7"

5Mpx (2560x1936)

Output 4in1

2.8mm lens

0 Lux

IR Range 20 m

3D DNR

IR Cut

Mirror

HLC, BLC, AGC, DWDR

Weatherproof IP67

Anti-vandal IK10

Specifications

Brand	Safire Smart
Range	E1 High-quality, high-performance professional
Image sensor	1/2.7" CMOS
Maximum resolution	5 Mpx (2560x1936)
Resolution	5Mpx@20FPS
Lens	2.8 mm
Minimum illumination	0.01 Lux @(F1.2, AGC ON)
Infrared lighting	0 Lux / IR range up to 40 m (ICR)
Day / Night	Auto / Colour / BW (Black and White)
Video output	1 x BNC switchable between HDTV1 / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, 3D-DNR, AWB, ATW, BLC, AGC, Mirror, Smart IR
Lens Adjustment	3 Axis
Power	DC 12 V / 300 mA, 4W max
Degree of protection	Waterproof IP67, Anti-vandal IK10
Temp. operation	-30° C ~ +50° C
Material	Metal body and plastic bracket
Dimensions	82.8 (H) x 94.6 (Ø) mm
Weight	390 g