

# SF-T941G-3KE

Turret Camera ECO Range

Output 4 in 1 / Resolution 3K  
(2880x1620)

1/3" CMOS 3K (5Mpx 16:9)

3.6 mm Lens

IR Matrix LEDs IR Matrix LEDs

Range 20 m

Weatherproof IP67



Turret HDTVI, HDCVI, AHD and Analog Camera

ECO Range

1/3" CMOS

Resolution 3K (2880x1620)

Output 4in1

3.6 mm Lens

0 Lux

IR Matrix Range 20 m

2D DNR

IR Cut

Weatherproof IP67

# Specifications

Range	ECO
Image sensor	3K 1/3" CMOS (5Mpx 16:9)
Maximum resolution	3K (2880x1620) to 20 fps
Resolution	TVI: 3K (20 fps) / 4 Mpx (15~30 fps) / 1080p (25~30 [%VAR%] fps) CVI: 4 Mpx (25~30 fps) / 1080p (25~30 [%VAR%] fps) AHD: 4 Mpx (15~30 fps) / 1080p (25~30 [%VAR%] fps) CVBS: PAL/NTSC
Lens	3.6 mm
Viewing Angle (FOV)	60° (H)
Minimum illumination	Colour: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Infrared lighting	0 Lux / IR Matrix LEDs (range 20 m)
Day / Night	Auto / Color / BW (black and white)
Video output	1 x BNC switchable between HDTV1 / HDCVI / AHD / CVBS
Video output switching	Via Switch
Basic functions	OSD menu (remote)
Configurable OSD functions	DWDR, 2D DNR, AE, ATW, AWB, BLC, Mirror, Flip
Alarm	No
Audio	No
Power	DC 12 V / 300 mA, 4 W max.
Degree of protection	Weatherproof IP67
Temp. operation	-10° C ~ +60° C
Material	Metal and plastic
Dimensions	68 (H) x 91 (Ø) mm
Base diameter	75 (Ø) mm / 4 screws
Weight	300 g