

XS-IPMCBOX-4

Main Box for X-Security mini cameras

4 Megapixel (2592x1944)

Has to be combined with a lens

Capacity for 3 streams

Compression

H.265+/H.265/H.264+/H.264

PoE IEEE802.3af



X-Security

Main Box for mini cameras

4 Megapixel (2688x1520)

Capacity for 3 streams

Compression H.265+/H.265/H.264+/H.264

RJ-45 10/100 BaseT

Perimeter protection, false alarm filter for vehicles and people

Face Capture: Compatible with facial recognition recorders

PoE IEEE802.3af

Audio

Alarms

SD card recording

Intelligent detection: faces, line crossing, intrusion, scene changes

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

Specifications

Brand	X-SECURITY
Maximum resolution	4 Megapixel (2592x1944)
Main Stream rate	2688×1520 (1–25 fps)
Extra Stream rate	Sub stream: 704×576 (1–25 fps) Third stream: 1920×1080 (1–25 fps)
Compression	H.265+/H.265/H.264+/H.264
Lens	Compatible with the lenses : XS-IPMC-4U-L1, XS-IPMC-4U-L3, XS-IPMC-4U-L4, XS-IPMC-4U-L5
Image improvements	BLC, HLC, DWDR, AWB, AGC, 3D-NR, MD, ROI, Mirror, Privacy Masking
Day / Night	Automatic electronic filter
Intelligent functions	Face detection, tripwire, area intrusion, scene changes & audio detection
Network interface	Ethernet 10/100 BaseT
Internal memory	SD Card slot, Max. 128GB
Alarms	2 Input / 2 Relay
Audio	1 Input / 1 Output
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Power	DC 12 V / 4.8W mA, PoE IEEE802.3af
Temp. operation	-40° C ~ 60° C
Degree of protection	Interior
Unit dimensions	110 mm (H) x 83 (W) x 24 (D) mm
Weight	210 g