

XS-IPMC005SWA-4P

4 MP IP Camera

1/3" CMOS Progressive Scan Starlight

Compression

H.265+/H.265/H.264+/H.264/MJPEG

Lens 2.8 mm | WDR (120 dB)

Minimum illumination 0.001 Lux

WEB, CMS Software, Smartphone

and NVR



X-Security

IP camera

1/3" CMOS Progressive Scan Starlight

4 Megapixel (2688x1520)

2.8 mm Pinhole Lens

Colour 0.01 Lux / B&W 0.001 Lux

Compression H.265+/H.265/H.264+/H.264

Intelligent detection: faces, line crossing, intrusion

WDR (120 dB)

Integrated microphone

RJ-45 10/100 BaseT

ONVIF Compatible

Web interface, CMS (DSS/PSS) and smartphone

Specifications

Brand	X-SECURITY
Image sensor	1/3" Progressive Scan CMOS
Resolution	4 Megapixel (2688×1520)
Main Stream rate	2688×1520 (1 ~ 20 FPS))
Sub Stream Rate	704×576 (1–25 fps)
Compression	H.265+, H.265, H.264+, H.264
Lens	2.8 mm
Minimum illumination	Color 0.001 Lux 1/3s @ F1.6
Image improvements	WDR, ROI, AWB, 3DNR, MD, Mask, Mirror
Internal memory	No
Alarms	No
Audio	1 Integrated microphone, 1 IN / 1 OUT
Network interface	Ethernet 10/100 BaseT
Remote access	Web browser, Smartphone App & PC Software
Interoperability	ONVIF, PSIA, CGI
Power	DC 12 V / 150 mA max.
Degree of protection	Suitable for interior
Temp. operation	-40° C ~ +60° C
Dimensions	57,7 (H) x 44,9 (W) x 34,35 (D) mm
Weight	81 g