

XS-IPT987ZSWH-4P-W

X-Security IP Turret Camera
4 Megapixel (2560×1440)
Wi-Fi 2.4G built-in dual antenna Wi-Fi
2.8mm lens
Microphone and speaker built-in
Weatherproof IP67



X-Security
IP camera
PRO Range
1/3" Progressive CMOS
4 Megapixel (2560 × 1440)
2.8 mm Lens
WIFI 2,4 G
Dual WIFI antenna
0.03 Lux
IR Array Range 30 m
Microphone and speaker built-in
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
DWDR
IR Cut
Weatherproof IP67
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/3" Progressive CMOS
Maximum resolution	2 Megapixel (2560×1440)
Lens	2.8 mm (H: 90°; V: 50°; D: 107°)
WIFI	IEEE802.11b/g/n 2,4–2,4835 GHz; 2,4 g
WIFI range	Up to 120 m (performance varies depending on actual environment)
Main Stream rate	2560 × 1440 (1–20 fps)
Extra Stream rate	704 × 576 (1–25 fps) 704 × 480 (1–30 fps)
Compression	H.265+/H.265/H.264+/H.264
Minimum illumination	0.03 Lux@F2.0 (Color, 30 IRE) 0.003 Lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)
Infrared lighting	IR LEDs (30 m)
Image improvements	dWDR, BLC, HLC, AWB, AGC, 3D-DNR, ROI , Smart IR
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Audio	Microphone and speaker built-in
Audio Compression	G.711a; G.711Mu
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF (Profile S/Profile T); .CGI; P2P
Power	DC 12V / 6.1W
Material	Inner core: Metal + Plastic Cover: Plastic
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP67
Dimensions	102.2 mm (D) x 109.9 (Ø) mm
Weight	352 g