

XS-IPB026A-4ESW

4 Megapixel IP Wifi camera
1/3" Progressive Scan CMOS
Compression H.265+
2.8 mm Lens
IR LEDs Range 30 m
WEB, DSS/PSS, Smartphone and
NVR



X-Security
IP camera
1/3" Progressive CMOS
4 Megapixel (2560×1440)
2.8 mm Lens
IR Range 30m
Audio: Integrated microphone and speaker
Compression H.265+/H.265/H.264/MJPEG
RJ-45 10/100 BaseT
Wifi IEEE 802.11b/g/n
Weatherproof IP67
Recording on SD card up to 128 GB
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible
ECO Range, a special low-cost IP camera

Specifications

Brand	X-SECURITY
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4Mpx (1 ~20 FPS)
Sub Stream Rate	704x576 (1 ~25 FPS)
Compression	H.265+ / H.265 / H.264 / H.264H / H.264B / MJPEG
Bitrate	9 Kbps ~ 4096 Mbps
Lens	2.8 mm (H: 100°)
Infrared lighting	0 Lux / IR LEDs (30 m)
Network interface	Ethernet 10/100 BaseT, Wi-Fi (802.11b/g/n)
Internal memory	Slot for MicroSD card, Max 128 GB
Alarms	No
Audio	1 Built-in microphone, 1 Speaker
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Power	DC 12V / 6.2W
Degree of protection	Weatherproof IP67
Temp. operation	-40° C ~ +60° C
Dimensions	180 mm (H) x 83.3 mm (W) x 114.8 mm (D)
Weight	350 g