

# XS-IPB830ZSWH-4P-AI-BLACK

X-Security IP Bullet Camera Black  
4 Megapixel (2560 × 1440)  
Lens 2.7–13.5 mm / LEDs Range 60  
m  
WDR 120 dB | Integrated Microphone  
PoE | H.265+  
Intelligent functions



X-Security  
IP Bullet Camera  
PRO Range  
WizSense  
1/2.9" Progressive CMOS  
4 Megapixel (2560 × 1440)  
2.7~13.5mm Motorised Lens  
0.006 Lux  
IR60 m  
Compression H.265+/H.265/H.264+/H.264  
RJ-45 10/100 BaseT  
PoE IEEE802.3af  
IVS  
Intelligent search  
SMD Plus  
Built-in microphone  
WDR 120dB  
IR Cut  
Weatherproof IP67  
Vandal proof IK10  
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR  
ONVIF Compatible  
Black colour

# Specifications

Brand	X-SECURITY
Maximum resolution	4 Megapixel (2560x1440)
Image sensor	1/2.9" Progressive CMOS
Lens	2.7 mm–13.5 mm (H: 104°–29°; V: 54°–16°; D: 125°–34°)
IR range	60 m
Main Stream rate	2688 × 1520@(1–20 fps)/2560 × 1440@(1-25/30 fps)
Extra Stream rate	704 × 576@(1–25 fps)/704 × 480@(1–30 fps)
Compression	H.265; H.264; H.264H; H.264B; MJPEG
Range performance	64-210 (D), 25.6-84 (O), 12.8-42 (R), 6.4-21 (I)
Minimum illumination	0.006 lux@F1.5 (Colour, 30 IRE) 0.0006 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)
Image improvements	WDR 120 dB, BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
Intelligent search	Work together with Smart NVR to refine intelligent search, event extraction and merging with event videos
Network interface	Ethernet 10/100 BaseT
Audio	Built-in microphone
Audio Compression	G.711a; G.711Mu; PCM; G.726
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Material	Metallic
Interoperability	ONVIF (Profile S/Profile T); CGI
Power	DC 12 V / 3,1W, PoE IEEE802.3af
Color	Black
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP67, Vandal-proof IK10
Dimensions	238.5 mm (D) x 90.7 (Ø) mm
Weight	730 g