

XS-IPD744WA-4U-AI

X-Security WizSense IP Dome

Camera

4 Megapixel (2688 × 1520)

2.8 mm Lens

IR LED 50m | Built-in Microphone

H.265+ | PoE

Weatherproof IP67 Anti-vandal IK10



X-Security

IP Turret Camera

ULTRA Range

WizSense

1/2.9" Progressive CMOS

4 Megapixel (2688 × 1520)

2.8 mm Lens

0.005 Lux

IR LED Range 50 m

Compression H.265+/H.265/H.264+/H.264

RJ-45 10/100 BaseT

PoE IEEE802.3af

Weatherproof IP67

Built-in microphone

IVS (Perimeter Protection)

SMD Plus

WDR (120 dB)

IR Cut

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/2.9" CMOS image sensor
Maximum resolution	4 Megapixel (2688 × 1520)
Lens	2.8 mm (H: 102°; V: 54°; D: 121°)
IR range	50 m
Range performance	63.6 (D), 25.4 (O), 12.7 (R), 6.4 (I)
Main Stream rate	2688 × 1520 @ (1–25/30) fps
Extra Stream rate	704 × 576 @ (1–25 fps)/704 × 480 @ (1–30 fps)
Compression	H.265; H.264; H.264H; H.264B; MJPEG
Minimum illumination	0,005 lux@F1,4 (color, 30 IRE) 0,0005 lux@F1,4 (black and white, 30 IRE) 0 lux (illuminator on)
Video bit rate	H.264: 3 kbps–8192 kbps H.265: 3 kbps–8192 kbps
Lens Adjustment	3 Axis
Image improvements	WDR (120 dB), BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
AI SSA	Yes
Weight	500 g
Network interface	Ethernet 10/100 BaseT
Audio	Built-in microphone
Audio Compression	G.711a; G.711Mu; G.726; PCM
External storage	256 GB microSD card slot
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF (Profile S/Profile G); .CGI; P2P
Power	DC 12 V / 4.2 W, PoE IEEE802.3af
Temp. operation	-40° C ~ +60° C
Material	Metallic
Degree of protection	Weatherproof IP67
Dimensions	93.6 mm (D) x 106 (Ø) mm