

XS-IPB225-4U-FC-AI-BLACK

X-Security WizSense Turret IP

Camera BLACK

4 Megapixel (2688 × 1520)

2.8 mm Lens

PoE | H.265+

Built-in microphone | Micro SD up to

256GB

Intelligent Functions : Smart Dual

Illumination



X-Security

Turret IP Camera

PRO Range

1/2.9" Progressive CMOS

4 Megapixel (2688 × 1520)

2.8 mm autofocus lens

Smart Dual Lighting

0.008 Lux

IR Array Range 30 m

White Light 30m

Compression H.265+/H.265/H.264+/H.264

Integrated microphone

RJ-45 10/100 BaseT

PoE IEEE802.3af

Smart function: Intrusion, tripwire (both functions support accurate classification and detection of vehicles and persons)

SMD Plus

MicroSD card up to 256GB

WDR

IR Cut

Weatherproof IP67

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

Black colour

Specifications

Brand	X-SECURITY
Image sensor	1/2.9" Progressive CMOS
Maximum resolution	4 Megapixel (2688 x 1520)
Main Stream rate	2688 x 1520@(1–20 fps)/2560 x 1440@(1–25/30 fps) Sub stream: 704 x 576@(1–25 fps)/704 x 480@(1–30 fps)
Compression	H.264H; H.265; H.264; H.264B; MJPEG
Lens	2,8 mm: H: 95°; V: 52°; D: 114°
Minimum illumination	0,008 lux@F1,6 (color, 30 IRE) 0,0008 lux@F1,6 (black and white, 30 IRE) 0 lux (illuminator on)
Image improvements	WDR, BLC, HLC, AWB, AGC, 3D-DNR, ROI , Smart IR, Mirror
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
Intelligent search	Work together with Smart NVR to refine intelligent search, event extraction and merging with event videos
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Audio	Integrated microphone
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Material	Inner core: Metallic Cover: Plastic
Colour	Black
Power	DC 12 V / 5,2W, PoE IEEE802.3af
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP67
Dimensions	100,9 mm (D) x 109,9 (Ø) mm
Weight	560 g