

XS-IPT987ZSWH-4U-AI

Turret IP Camera X-Security ULTRA
Range
4 Megapixel (2688x1520)
2.7 ~ 13.5 mm varifocal lens
Motorised Autofocus
PoE | H.265+ | Integrated microphone
Weatherproof IP67



X-Security
IP camera
ULTRA Range
WizSense
1/2.9" Progressive CMOS
4 Megapixel (2688x1520)
2.7~13.5 mm motorised varifocal autofocus lens
0.005 Lux
IR Array Range 40 m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP67
IVS (Perimeter Protection)
WDR 120dB
IR Cut
Built-in microphone
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/2.9" Progressive CMOS
Maximum resolution	4 Megapixel (2688x1520)
Main Stream rate	2688 × 1520 @ (1–25/30) fps
Extra Stream rate	704 × 576 @ (1–25 fps)/704 × 480 @ (1–30 fps)
Compression	H.265+/H.265/H.264+/H.264
Lens	2.7 ~ 13.5 mm (H: 104°-29°)(V:54°-16°)(D:125°-33°)
Minimum illumination	0.005 lux@F1.5 (Color, 30 IRE) 0.0005 lux@F1.5 (B/W, 30 IRE) 0 lux (Illuminator on)
Image improvements	WDR 120dB, BLC, HLC, AWB, AGC, 3D-NR, ROI , Smart IR
IVS (Perimeter protection)	Tripwire, intrusion (supports accurate classification and detection of vehicles and persons)
AI SSA	Yes
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Audio	Integrated microphone
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF (S Profile /G Profile /T Profile); .CGI; P2P; Milestone; Genetec
Power	DC 12 V / 5.2W, PoE IEEE802.3af
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP67
Dimensions	108,3 mm (D) x 122 (Ø) mm
Weight	715 g