

XS-IPB619SWH-8P-AI

Bullet IP Camera 8 Megapixel Pro
Range
1/2.7" Progressive Scan CMOS
Compression
H.265+/H.265/H.264+/H.264
Lens 2.8 mm / LEDs Range 30 m
WDR | Integrated microphone
Smart Features



X-Security
IP Bullet Camera
PRO Range
1/2.7" Progressive CMOS
8 Megapixel (3840 x 2160)
2.8 mm Lens
0.009 Lux
IR 30m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE IEEE802.3af
Weatherproof IP67
IVS
Intelligent search
Built-in microphone
WDR
3D DNR
IR Cut
SD card recording
WEB Interface, CMS (DSS/ PSS), Smartphone and NVR
ONVIF Compatible

Specifications

Brand	X-SECURITY
Image sensor	1/2.7" Progressive CMOS
Maximum resolution	8 Megapixel (3840 × 2160)
Lens	2.8 mm (H: 106°; V: 56°; D: 125°)
Main Stream rate	3840 × 2160@(1–20 fps)/2688 × 1520@(1–25/30 fps)
Extra Stream rate	7704 × 576@(1–25 fps)/704 × 480@(1–30 fps)
Compression	H.264H; H.265; H.264; H.264B; MJPEG (substring compatible only)
Intelligent codec	Smart H.265+; Smart H.264+
Infrared lighting	0.008 lux@F1.6 (Color, 30 IRE) 0.0008 lux@F1.6 (B/W, 30 IRE) 0 lux (Illuminator on)
Range performance	88 (D), 35.2 (O), 17.6 (R), 8.8 (I)
Image improvements	WDR 120dB, BLC, HLC, AWB, AGC, 3D-DNR,
IVS (Perimeter protection)	Intrusion, tripwire (both functions support the accurate classification and detection of vehicles and persons)
Intelligent search	Work together with Smart NVR to refine intelligent search, event extraction and merging with event videos
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Audio	Integrated microphone
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Material	Metallic
Power	DC 12 V / 3,4W, PoE IEEE802.3af
Temp. operation	-40° C ~ +60° C
Internal memory	Micro SD Max 256GB
Degree of protection	Weatherproof IP67
Dimensions	166,2 mm × 70 mm × 70 mm (L × W × H)
Weight	480 g