

# XS-T744SWA-5P4N1

X-Security Turret Camera PRO Range

Output 4in1

1/2.7" CMOS

2.8 mm Lens | 60 m IR range

Audio over Coaxial cable in HDCVI

Weatherproof IP67



X-Security

Turret HDTVI, HDCVI, AHD and Analog Camera

PRO Range

High Performance CMOS

HD 5Mpx (2560x1944)

Output 4in1

2.8 mm Lens

0 Lux

IR Matrix Range 60 m

Audio over Coax in HDCVI

IR Cut

Weatherproof IP67

# Specifications

|                            |  |
|----------------------------|--|
| Brand                      | X-Security   |
| Range                      | PRO  |
| Image sensor               | 1/2.7" CMOS  |
| Maximum resolution         | 5 Mpx (2560x1944)                                      |
| Resolution                 | 5Mpx to 25 fps,4Mpx to <25 fps, 1080P to 25 fps        |
| Lens                       | 2.8 mm   |
| Minimum illumination       | 0.01 Lux @(F1.6, AGC ON)                               |
| Infrared lighting          | 0 Lux / SMART IR (60 m)                                |
| Day / Night                | Auto / Colour / BW (Black and White)                   |
| Audio                      | Built-in microphone (Audio via coaxial cable in HDCVI) |
| Video output               | 1 x BNC switchable between HDTVI / HDCVI / AHD / CVBS  |
| Video output switching     | Via Switch   |
| Basic functions            | OSD menu (remote)                                      |
| Configurable OSD functions | DWDR, 2D-DNR, HLC, BLC, Mirror, Smart IR               |
| Lens Adjustment            | 3 Axis   |
| Power                      | DC 12 V / 434 mA, 5.2 W max                            |
| Degree of protection       | Weatherproof IP67                                      |
| Temp. operation            | -40° C ~ +60° C  |
| Material                   | Metallic   |
| Dimensions                 | 99.1 (H) x 121.9 (Ø) mm                                |
| Base diameter              | 83.3 (Ø) mm / 3 screws                                 |
| Weight                     | 400 g  |