

# XS-D843W-8P4N1

HDTVI, HDCVI, AHD and Analog X-

Security Dome Camera

1/2.7" CMOS 8 Megapixel

2.8 mm Lens

WDR (120dB)

IR 30m

Waterproof IP67 | Anti-vandal IK10



X-Security

HDTVI, HDCVI, AHD and Analog Dome Camera

PRO Range

1/2.7" CMOS

8Mpx (3840x2160)

Output 4in1

2.8 mm Lens

B/W 0 Lux

IR Array Range 30 m

WDR (120dB)

IR Cut

Weatherproof IP67

Vandal proof IK10

# Specifications

Brand	X-Security
Image sensor	1/2.7" Progressive CMOS
Maximum resolution	8 Megapixel (3840x2160)
Main Stream rate	8 Mpx(1 ~ 15fps),5 <Mpx(1 ~ 20fps),4 Mpx(1 ~ 25/30fps)
Lens	2.8 mm (H105°)
Minimum illumination	0.03Lux/F1.7 (Color, 1/30s,30IRE)
Infrared lighting	0 Lux / IR LEDs Array (30 m)
Image improvements	WDR, Smart IR, BLC, HLC, AWB, AGC, 3D-NR, Privacy Masking, Motion Detection, ROI
Day / Night	Removable mechanical ICR filter
Alarm	No
Audio	No
Power	DC 12 V / 400 mA
Degree of protection	Waterproof IP67   Anti-vandal IK10
Temp. operation	-40° C ~ +60° C
Dimensions	110 (Ø) x 81 (h) mm
Weight	320 g