

XS-NVR2104-4K4PH

X-Security NVR for IP cameras
4 CH IP and 4 PoE ports
Maximum recording resolution 8 Mpx
Compression H.265 / H.264
Outputs 4K HDMI & VGA
Supports 1 hard disk



X-Security
NVR for IP cameras
4 CH
80 Mbps bandwidth supported
Maximum resolution 8 Megapixel
Compression H.265 / H.264
VGA and HDMI 4K output
IP Dual Stream Access
Mouse
Space for 1 HDD
4 PoE ports IEEE802.3af/at
WEB, CMS (DSS/PSS), Smartphone and NVR interface
ONVIF Compatible

Specifications

| | |
|----------------------------|--|
| Brand | X-SECURITY |
| Inputs for IP cameras | LAN port up to 4 channels |
| PoE | Switch of 4 PoE channels IEEE802.3af/at |
| IP compatible cameras | X-SECURITY (proprietary protocol), HIKVISION, SAFIRE, ONVIF |
| Video outputs | 1 HDMI 4K, 1 VGA |
| Bidirectional audio | 1 input, 1 output, RCA |
| Video compression format | H.265 / H.264 |
| Display resolution | 3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768 |
| Total bandwidth | 80 Mbps |
| Recording resolution | 8Mp, 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 720P, D1... |
| Simultaneous multifunction | Pentaplex: Live, Recording, Playback, Backup and Remote Access |
| Alarms | No |
| Recording method | Manual, programmed, motion detection |
| Backup | USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA internal interface |
| Internal memory | 1 SATA HDD 3.5" of up to 6 TB (not included) |
| Communication | 2x USB 2.0 (Mouse and backup) /1 RJ45 10/100M (Ethernet) |
| Remote access | Browser (ActiveX), mobile app or softwarePSS |
| Power supply | DC 48 V / 1.25 A |
| Dimensions | 1U, 48 (H) x 260 (W) x 225 (D) mm / 0.8 Kg (without HDD) |