

# XS-NVR2108-S38P

X-Security AI IP Recorder

8 CH IP video / 8 PoE ports

Maximum recording resolution 12 Mpx

Bandwidth 80 Mbps

Full HD HDMI and VGA Output

Supports 1 hard disk



X-Security

AI IP Recorder

8 CH

80 Mbps bandwidth supported

Supports Perimeter protection and SMD Plus

Maximum resolution 12 Mpx

Compression Smart H.265 / H.265 / Smart H.264 / H.264

VGA and HDMI Full HD outputs

1 HDD

8 PoE ports

WEB, CMS (DSS/PSS), Smartphone and NVR interface

ONVIF Compatible

# Specifications

Brand	X-SECURITY
Inputs for IP cameras	LAN port up to 8 channels
PoE	8 PoE ports IEEE802.3at/af
Video outputs	1 HDMI Full HD, 1 VGA
Bidirectional audio	1 input, 1 output, RCA
Video compression format	Smart H.265 / H.265 / Smart H.264 / H.264
Decoding capacity	1-channel 12MP@30 fps; 1-channel 8MP@30 fps; 2-channel 5MP@30 fps; 3-channel 4MP@30 fps; 6-channel 1080p@30 fps
Total bandwidth	80 Mbps record
Recording resolution	12MP / 8MP /5MP / 4MP / 3MP / 2MP / 720p / D1
ONVIF	T/S/G Profile
AI functions	Perimeter protection / SMD Plus
Perimeter performance of AI per camera (Number of Channels)	4
SMD Plus through camera	SMD Plus of 4 channels (AI per camera), secondary filtering for humans and motor vehicles
Internal memory	1 SATA HDD 3.5" of up to 16 TB (not included)
Communication	2x USB 2.0 (Mouse and backup) /1 RJ45 10/100M (Ethernet)
Remote access	Web browser, mobile phone application or PSS software
Power	DC 48 V-53 V / 2.0 A
Dimensions	47,6 (H) x 260 (W) x 232,7 (D) mm / 1,94 Kg (without HDD)