

XS-XVR6104S-4KL-FACE

DVR 5n1 X-Security

4 CH analog (8Mpx) + 4 IP (8Mpx)

Audio over coaxial

4K (7FPS) Recording Resolution

2 CH facial recognition

4 CH Human and vehicle recognition



X-Security

DVR 5n1

4 CH video HDTVI/HDCVI/AHD/CVBS / 4+4 IP / 1 CH audio

H.265+ / H.265 / H.264+ / H.264

8M Recording resolution (7FPS) 6M / (10FPS) 5M / (12FPS) 4K-N, / 4MP, 3MP(15fps) 4M-N / 1080P or 720P or 960H or D1 or CIF (25/30fps)

PTZ Control (RS485/Coaxial)

Audio over coaxial

HDMI Full HD, VGA & CVBS Outputs

2 CH facial recognition

Human and Vehicle Recognition (Available for 4 CH coaxial video)

Compact size

Mouse

2 USB Ports

Space for 1 HDD

POS functions

Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 8 IP Channels (8Mpx), replacing all the BNC channels
Video outputs	1 HDMI 4K, 1 VGA
Video / audio compression	H.265+ / H.265 / H.264+ / H.264
Display resolution	HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720
Total bandwidth	64 Mbps
Recording resolution	8M (7FPS) / 6M (10FPS) / 5M (12FPS) / 4K-N, 4MP, 3MP(15fps) / 4M-N or 1080P or 720P or 960H or D1 or CIF (25/30fps)
Main Stream coding	8M (7FPS) / 6MP(10FPS) / 5MP(12FPS) / 4K-N, 4MP, 3MP(15FPS) / 4M-N, 1080P, 720P, 960H, D1, CIF (25/30FPS)
Extra Stream coding	960H(15FPS) / D1, CIF(25/30FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Alarms IN/OUT	No
Video analysis	IVS: Face detection / People and vehicle recognition / Line crossing / Intrusion
Facial recognition	1 live analogue face comparison channel
Intelligent motion detection	Up to 4 channels capable of classifying targets amongst humans and vehicles
Recording method	Manual, programmed, motion detection, alarm
Backup	USB / Network
Internal memory	1 SATA HDD 3.5" of up to 10 TB (not included)
Communication	RS485 (PTZ) /2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12V / 2A
Dimensions / Weight	48 (H) x 260 (W) x 238 (D) mm / 1.1 Kg