

XS-XVR3104-HV

DVR 5n1 X-Security

4 CH HDTVI / HDCVI / AHD / CVBS /

4+1 IP

1080N/720P (25FPS) | H.265+| SMD+

Audio 1 entrada/1 output by RCA

Full HD and VGA HDMI output

Supports 1 hard disk



X-Security

XVR 5n1

4 CH HDTVI/HDCVI/AHD/CVBS video / 4+1 IP / 1 CH two-way RCA audio

Compression H.265+/H.265/H.264+/H.264

Resolution up to 1080N/720P

SMD PLUS

Audio

HDMI & VGA Output

Mouse

Space for 1 HDD SATA 6 TB

Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	4 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 5 IP Channels (6Mpx), replacing all the BNC channels
Video outputs	1 HDMI full HD and 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.265+/H.265/H.264+/H.264
Display resolution	1920x1080, 1280x1024, 1280x720
SMD PLUS	Filtering of false alarms of people and vehicles in movement detection
Recording resolution	1080N; 720p; 960H; D1; HD1; [%VAR%] BCIF; CIF
Main Stream coding	First channel: 1080N, 720p (1~25/30FPS), Rest of channels: 1080N, 720p (1~15FPS) / 960H, D1,CIF (1~25/30 FPS)
Extra Stream coding	CIF (1~7 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Intelligent functions	POS Function Bidirectional Audio by RCA
Alarms	No
Recording method	Manual, programmed, motion detection (up to 396 zones)
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 6TB (not included)
Communication	2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12 V / 1.5 A
Dimensions / Weight	260.0 (An) × 237.9 (Fo) × 47.6 (An) mm