

XS-XVR3108-HV

DVR 5n1 X-Security

8 CH HDTV I / HDCVI / AHD / CVBS /

8+2 IP

1080N (25FPS) | H.265+| SMD+

Audio 1 entrada/1 output by RCA

Full HD and VGA HDMI output

Supports 1 hard disk



X-Security

XVR 5n1

8 CH video HDTV I/HDCVI/AHD/CVBS / 8+2 IP / 1 CH bidirectional audio

Compression H.265+/H.265/H.264+/H.264

Resolution up to 1080N

SMD PLUS

Audio

HDMI & VGA Output

Mouse

Space for 1 HDD SATA 6 TB

Specifications

Brand	X-Security
Video format	HDTV / HDCVI / AHD / CVBS / IP
Video inputs	8 Channels BNC (HDTV / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 10 IP Channels (6Mpx), replacing all the BNC channels
Video outputs	1 HDMI full HD and 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Video / audio compression	H.265+/H.265/H.264+/H.264
Display resolution	1920x1080, 1280x1024, 1280x720
SMD PLUS	Filtering of false alarms of people and vehicles in movement detection
Recording resolution	1080N; 720p; 960H; D1; HD1; [%VAR%] BCIF; CIF
Main Stream coding	First channel: 1080N, 720p (1~25/30FPS), Rest of channels: 1080N, 720p (1~15FPS) / 960H, D1, CIF (1~25/30 FPS)
Extra Stream coding	CIF (1~7 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Intelligent functions	POS Function Bidirectional Audio by RCA
Alarms	No
Recording method	Manual, programmed, motion detection (up to 396 zones)
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 6TB (not included)
Communication	2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12 V / 1.5 A
Dimensions / Weight	47.6 (H) x 260 (W) x 237.9 (D) mm / 0.89 Kg