

# XS-XVR3116-H

DVR 5n1 X-Security

16 CH HDTVI / HDCVI / AHD / CVBS

/ 16+2 IP

6 Mpx in IP, 1080N and 720P

(25FPS) in analog

RCA Audio Input and Output

Full HD HDMI and VGA Output

Supports 1 hard disk



X-Security

DVR 5n1

16 CH video HDTVI/HDCVI/AHD/CVBS / 16+2 IP / 1 CH audio

H.265/H.264

Recording resolution per channel: 1080N (25FPS) in the channel 1, 1080N/720p (15FPS) in the other channels

PTZ Control (via Coaxial and RS485)

Audio Channel

Full HD HDMI and VGA Output

Mouse

Space for 1 HDD

# Specifications

Brand	X-Security
Video format	HDTV / HDCVI / AHD / CVBS / IP
Video inputs	16 Channels BNC (HDTV / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 18 IP channels (6Mpx)
Video outputs	1 HDMI Full HD, 1 VGA
Audio inputs	1 Channel RCA
Audio outputs	1 Channel RCA
Video / audio compression	H.265/H.264 / G.711u/G.711A/PCM
Display resolution	1920x1080, 1280x1024, 1280x720, 1024x768
Recording resolution	1080p / 720p / 1080N / 960H / D1 / HD1 / BCIF / CIF / QCIF
Main Stream coding	First channel: 1080N (1~25FPS), Other channels: 1080N/720p (1~15FPS) / 960H / D1 / CIF / (1~25FPS)
Extra Stream coding	D1 / CIF / QCIF (1~7FPS)
Recording method	Manual, programmed, motion detection
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network
Internal memory	1 HDD SATA 3.5" of up to 10TB (not included)
Communication	RS485 (PTZ) / 2 x USB (Mouse and backup) / RJ45 100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power supply	DC 12 V / 2 A
Dimensions / Weight	48 (H) x 260 (W) x 236 (D) mm / 1.7 Kg