

# XS-XVR6232S-AI

DVR 5n1 X-Security

32 CH HDTV/HD/HD/HD/ up  
to 32CH IP (5M-N)

2 CH facial recognition

16 CH Human and vehicle recognition

5M-N/1080p(10FPS) Recording

Resolution

Audio All-over-Coax



X-Security

DVR 5n1

32 CH video HDTV/HD/HD/HD / 32 IP / 1 CH audio

H.265+/H.265

2 CH facial recognition

Human and Vehicle Recognition (Available for 16 CH coaxial video)

Resolution per channel: 5M-N (1~10fps) 4M-N/1080p (1~15FPS) 1080N/720p (25~30FPS)

PTZ Control (RS485/Coaxial)

All-over-Coax two-way audio

Full HD HDMI, VGA and BNC output

Mouse

Space for 2 HDD

POS

# Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	32 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 32 IP Channels (6Mpx), replacing all the BNC channels
Video outputs	1 HDMI 4K, 1 VGA
Video / audio compression	H.265+/H.265/H.264+/H.264 / G.711u
Display resolution	3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720
Total bandwidth	128 Mbps
Recording resolution	5M-N, 4 M-N, 1080p, 720p, 960H, D1, CIF
Main Stream coding	5M-N(10 fps), 4M-N/1080p(15 fps), 720p (30 fps)
Extra Stream coding	D1 / CIF / QCIF (1~15 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Audio	1 in / 1 out RCA
Bidirectional audio	Reusing the audio input/output
Video analysis	IVS: Tripwire   Area intrusion   Abandoned object   Face detection
	IP Mode, Face Recognition and IVS cannot be enabled at the same time
Intelligent functions	Function P2P   POS function   Alarm / audio / update by Coaxial (All-over-Coax)
Intelligent motion detection	Up to 16 channels capable of classifying targets amongst humans and vehicles
Recording method	Manual, programmed, motion detection, alarm, stop
Backup	USB / Network
Internal memory	2 SATA HDD up to 10TB (not included)
Communication	RS485 (PTZ) /3 x USB (Mouse and backup) / RJ45 10/100/1000 (Ethernet)
Remote access	Web browser, mobile phone application or PSS software
Power	DC 12V / 5A
Dimensions / Weight	288 (H) x 375 (W) x 53 (D) mm / 2.0 Kg