

DAHUA-2991

DH-HAC-HFW1500CP-A-0280B-S2



DAHUA 5MP 4 IN 1 CAMERA WITH SMART IR 30M



- 4-in-1 PRO series bullet camera with 30 m Smart IR for outdoor use
- 5MP 1/2.7" CMOS
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switchable via OSD
- Fixed 2.8 mm (111°) optics
- 0.005 lux
- ICR filter
- OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, digital Defog, Mirror, privacy masks
- Built-in microphone
- IP67
- 3AXIS
- 12V DC.



Reference / Model	DAHUA-2991 / DH-HAC-HFW1500CP-A-0280B-S2
-------------------	------------------------------------------

Specifications

DAHUA 5MP 4 IN 1 CAMERA WITH SMART IR 30M**Reference / Model****DAHUA-2991 / DH-HAC-HFW1500CP-A-0280B-S2**

5-megapixel 1/2.7" CMOS sensor

Digital resolution: 5MP (2880x1620), 4MP (2560x1440), 1080P (1920x1080), 960H (960x576)

Frames per second: 25 fps @5MP (CVI), 25 fps @4MP (CVI/TVI/AHD), 25 fps @1080P (CVI)

4 in 1 output switchable via OSD menu

Day/Night mode with removable mechanical filter (ICR)

0.005 lux F1.6 (colour) / 0 Lux IR On

Smart IR: 3 LEDs, up to 30 meters

2.8 mm fixed optics

Viewing angle: 111°(H), 58°(V), 132°(D)

OSD via coax (5MP video up to 700 meters).

Picture modes: BLC, HLC, digital WDR, 2D-NR, Mirror

Auto and manual white balance

Automatic and manual gain control

Supports 8-zone privacy masking

Built-in microphone

Power supply: 12V DC (±30%)

Power consumption: 3.7W (max.)

Storage temperature -40°C ~ +60°C (-40°C ~ +60°C)

Operating temperature from -40°C ~ +60°C

Relative humidity: <95% (non-condensing)

Degree of protection IP67

Plastic housing

Dimensions: 69,7 (W) x 70,2 (H) x 161,3 mm

Weight: 190 g

3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)

Power supply not included