

HWN-4216MH-16P

NVR for IP cameras

16Ch video / 16 PoE Port(s)

Max Resolution 8.0 Mpx /

Compression H.265+

Bandwidth 80 Mbps

Outputs 4K HDMI & VGA

Space for 2 hard disks



Hikvision HiWatch Series

NVR for IP cameras

16 CH

80 Mbps bandwidth supported

Maximum resolution 8 Megapixel

Compression H.265+/H.265/H.264+/H.264

Outputs 4K HDMI & VGA

IP Dual Stream Access

Mouse

Space for 2 HDD

16 PoE ports IEEE802.3af/at

WEB, CMS and Smartphone interface

ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Inputs for IP cameras	LAN port up to 16 channels
Power over Ethernet	16 port PoE Switch IEEE802.3af/at (max. 150 W)
IP compatible cameras	HIKVISION, ONVIF
Bidirectional audio	1 input / 1 RCA output
Video outputs	1 HDMI 4K, 1 simultaneous VGA
Video compression format	H.265+ / H.265 / H.264+ / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	160 Mbps downstream / 80 Mbps upstream
Main Stream recording	8MP/6MP/5MP/4MP/3MP/1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	No
Recording method	Manual, programmed, motion detection, alarm
External Backup	USB memory / HDD USB / CD-RW USB / DVR-RW USB
Internal memory	2 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 10/100/1000 (Ethernet)
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Power	AC 100~240 V, 50/60 Hz
Dimensions / Weight	52 (H) x 385 (W) x 315 (D) mm / 3.0 Kg (without HDD)