

DAHUA-3293-FO

DH-IPC-HFW1430DTP-STW-0280B



Dahua 4MP outdoor Wi-Fi IP camera



- Dahua Wi-Fi IP Camera
- 4MP@20ips, Smart H.265+/Smart H.264+
- ICR, 0.03/0.003 lux, Smart IR 30m
- 2.8mm optics
- Digital WDR, 3D-DNR
- Includes microphone and speaker
- MicroSD slot, RJ45, WiFi with dual antenna, Onvif, IP67, 3AXIS



Reference / Model

DAHUA-3293-FO / DH-IPC-HFW1430DTP-STW-0280B

1/3" 4 megapixel CMOS sensor

Compression formats: Smart H.265+, H.265, Smart H.264+, H.264

Digital Resolution: 4MP (2560x1440), 3MP (2304x1296), 1080P (1920x1080), 1.3MP (1280x960), 720P (1280x720)

Stream 1: 4MP (1~20fps)

Stream 2: D1 (1~25/30fps)

Day/night mode with removable mechanical filter

Smart IR: 1 led, range 30 meters

0.03 lux F2.0 (color), 0.003 lux F2.0 (B/W), 0 lux IR On

2.8mm fixed lens

View Angle: 90°(H), 50°(V), 107°(D)

Picture modes: BLC, digital WDR, 3D-NR, Mirror

White balance with 6 modes

Automatic gain control

Dahua 4MP outdoor Wi-Fi IP camera

Reference / Model**DAHUA-3293-FO / DH-IPC-HFW1430DTP-STW-0280B**

Supports 4-zone video sensor

Includes microphone and speaker

MicroSD card slot up to 256GB (not included)

Network interface: RJ45 (10/100 Base-T)

Network protocols: IPv4, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, DHCP, DNS, NTP, Multicast, RTMP

Incorporates Wi-Fi IEEE802.11b/g/n at 2.4GHz

Compatible with ONVIF (Profile S/T), CGI, P2P, SDK and API

Up to 6 users

Remote viewing via IE, Chrome and Firefox browsers

Smart PSS, DSS, DMSS management software

Compatible with IOS and Android mobile devices

Power: 12V DC

Consumption: 2.1W (basic), 6.1W (maximum)

Storage temperature -40°C ~ +60°C

Operating temperature -30°C ~ +60°C

Relative humidity: ≤95%

Degree of protection IP67

metal and plastic casing

Dimensions: 83.3 (W) x 114.4 (H) x 172.4 mm

Weight: 350g

3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)