

## DAHUA-2907

HAC-HFW2501EP-A-0280B-S2



### DAHUA 4-IN-1 BULLET CAMERA 5MP WITH SMART IR 40M



- 4-in-1 PRO series bullet camera with 40 m Smart IR for outdoor use
- 5MP 1/2.7" CMOS
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switchable via DIP switch
- Fixed 2.8 mm (111°) optics
- 0.001 lux
- ICR filter
- OSD, AWB, AGC, BLC, HLC, WDR 120dB, 2D/3D-NR
- Built-in microphone
- IP67
- 3AXIS
- 12V DC.



**Reference / Model**

**DAHUA-2907 / HAC-HFW2501EP-A-0280B-S2**

**Specifications**

**DAHUA 4-IN-1 BULLET CAMERA 5MP WITH SMART IR 40M****Reference / Model****DAHUA-2907 / HAC-HFW2501EP-A-0280B-S2**

5 megapixel 1/2.7" CMOS sensor

Digital resolution: 5MP (2880x1620), 4MP (2560x1440), 1080P (1920x1080), 720P (1280x720)

Frames per second: 25 fps @5MP (CVI), 25 fps @4MP (CVI/TVI/AHD), 25 fps @1080P (CVI)

4-in-1 output switchable via DIP switch

Day/Night mode with removable mechanical filter (ICR)

0.001 lux F1.6 (colour) / 0 Lux IR On

Smart IR: 2 LEDs, up to 40 metres

2.8 mm fixed optics

Viewing angle: 111°(H), 58°(V), 132°(D)

OSD via coax (5MP video up to 700 metres).

Picture modes: BLC, HLC, HLC Pro, WDR 120dB, 2D/3D-NR, Mirror.

Auto and manual white balance

Automatic gain control

Built-in microphone

Power supply: 12V DC (±30%)

Power consumption: 5.9W (max.)

Storage temperature: -40°C ~ +60°C (-40°C ~ +60°C)

Operating temperature range -40°C ~ +60°C

Relative humidity: <95% (non-condensing)

Degree of protection IP67

Metal housing

Dimensions: 70 (W) x 70 (H) x 179.9 mm

Weight: 420 g

3AXIS: 0°~360°(PAN), 0°~90°(TILT), 0°~360°(Rotation)