

VANDAL DOME 4 IN 1 DAHUA 5MP WITH SMART IR 30M



- Dahua 4 in 1 fixed dome PRO series with Smart IR of 30 m vandal resistant for outdoor
- 1 / 2.7 "CMOS of 5MP
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switchable by OSD
- 2.8 mm (111 °) fixed lens
- 0.005 lux
- ICR filter
- OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, privacy masks
- IP67, IK10
- 3AXIS
- 12V DC



Reference / Model

DAHUA-2810 / HAC-HDBW1500E-S2

VANDAL DOME 4 IN 1 DAHUA 5MP WITH SMART IR 30M

Reference / Model

DAHUA-2810 / HAC-HDBW1500E-S2

Specs

1 / 2.7 "5 megapixel CMOS sensor

Digital resolution: 5MP (2880x1620), 4MP (2560x1440), 1080P (1920x1080), 960H (960x756)

Images per second: 25 ips @ 5MP (CVI), 25 ips @ 4MP (CVI / TVI / AHD), 25 ips @ 1080P (CVI)

4-in-1 output switchable via OSD

Day / night mode with removable mechanical filter (ICR)

0.005 lux F1.6 (color) / 0 lux IR On

Smart IR: 12 LEDs, up to 30 meters

2.8mm fixed lens

Angle of view: 111 ° (H), 58 ° (V), 132 ° (D)

OSD via coaxial (5MP video up to 700 meters)

Imaging modes: BLC, HLC, Digital WDR, 2D-NR, Mirror

Automatic and manual white balance

Automatic and manual gain control

Supports 8 zone privacy mask

Power supply: 12V DC ($\pm 30\%$)

Consumption: 3.5W (max.)

Storage temperature -40 ° C ~ + 60 ° C

-40 ° C ~ + 60 ° C operating temperature

Relative humidity: <95% (non-condensing)

Degree of protection IP67

IK10 vandal protection

Metal housing

Dimensions: Ø109.9 x 81 mm

Weight: 310g

3AXIS: 0 ° ~ 355 ° (PAN), 0 ° ~ 65 ° (TILT), 0 ° ~ 355 ° (Rotation)