

HWP-N5225IH-AE

2 MP Motorised IP Camera
1/2.8" Progressive Scan CMOS
Compression H.265+/H.265
4.8~120 mm Lens (25X) Auto Iris
SD card Recording | IR LEDs 150m
WDR (120dB) | 3DNR | BLC | HLC |



Hikvision HiWatch Series
PTZ IP Camera
Average speed 120°/segundo
25X Optical zoom
1/2.8" Progressive Scan CMOS
2 Megapixel (1920x1080)
4.8-120mm Varifocal Lens
IR Range 150 m
Compression H.265+/H.265/H.264+/H.264
RJ-45 10/100 BaseT
PoE+ 802.3at
Weatherproof IP66
IR Cut
WDR
SD card recording
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Bracket not included (see compatible brackets)

Specifications

Brand	Hikvision
Range	HiWatch Series
Resolution	1080p (1920x1080) at 25 FPS
Minimum illumination	0.005 Lux @ F1.6 (colour) / 0.001 Lux @ F1.6 (B/N)
Infrared lighting	Automatic IR LED's, range 150 metres
Compression	H.265+/H.265/H.264+/H.264; Smart: ANR and ROI
Lens	Varifocal 4.8 ~ 120.0 mm (Optical Zoom 25X)
Digital zoom	16 X
Electronic shutter	1/1s~1/30,000s
Day / Night	Removable mechanical ICR filter
Image improvements	BLC, HLC, WDR (120dB), 3D-NR, AGC, AWB, Motion Detection
Video analysis	VCA: Tripwire Area intrusion Audio exception
Pan/Tilt Range	Horizontal: 0°~360°, Vertical: -15°~90° auto flip 180°
Manual speed	Horizontal: 0.1° ~120°/s, Vertical: 0.1° ~80°/s
Speed between Presets	Horizontal: 120° /s, Vertical: 80° /s
Preset positions	300 preset, 4 auto pattern, 8 auto tour, auto pan, auto scan
Internal memory	MicroSD card, Max 256 GB
Audio	No
Alarms	No
PTZ Control	Through network access
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, API, PSIA, CGI
Power	AC 24 V / 1.5 A PoE+(802.3at, class4)
Temp. operation	-30° C ~ +65° C
Degree of protection	IP66 / Surges 4000V
Dimensions (without bracket)	345 mm (H) x 213 (Ø) mm
Weight (without bracket)	3300 g