

# HWI-D149H

4 Megapixel Hikvision IP Camera

1/2.8" Progressive Scan CMOS

ColorVu

Compression H.265+/H.265

2.8 mm Lens

Deterrent white light Range 30 m

WEB, CMS Software, Smartphone

and NVR



Hikvision HiWatch Series

IP Dome Camera

1/2.8" Progressive Scan CMOS ColorVu

4 Megapixel (2560x1440)

2.8 mm Lens

Color Image 24/7

WDR

3DNR

H.265+

RJ-45 10/100 BaseT

PoE IEEE802.3af

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

Weatherproof IP67

Vandal proof IK08

# Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4Mpx (20 FPS), 1080p / 720p (25 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Lens Adjustment	2 Axis
Minimum illumination	Colour 0.01 Lux @ F1.2   Colour 0.028 Lux @ F2.0
Visible lighting	0 Lux / Supplementary Light (White): 30 m
Image improvements	WDR, BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	No
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power	DC 12 V / 500 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67, Vandal-proof IK10
Material	Plastic
Temp. operation	-30° C ~ +50° C
Dimensions	97.6 mm (D) x 121.5 (Ø) mm
Weight	500 g