

HWI-B640H-Z

4 Megapixel Hikvision IP Camera
1/3" Progressive Scan CMOS
Compression H.265+ / H.265
2.8~12mm motorised auto-focus lens
EXIR IR LEDs range 30 m
WDR | 3DNR | BLC | IP67 | SD Slot



Hikvision HiWatch Series
IP camera
1/3" Progressive Scan CMOS
4 Megapixel (2560x1440)
2.8~12 mm motorised varifocal autofocus lens
0 Lux
IR Range 30 m
H.265+/H.265/H.264+/H.264
Dual stream
RJ-45 10/100 BaseT
PoE IEEE802.3af
SD card recording
Weatherproof IP67
IR Cut
WDR
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4Mpx (20 FPS) / 1080p / 720p (25 FPS)
Extra Stream rate	D1 / CIF (1 ~ 25 FPS)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm ~ 12 mm Motorised Autofocus
Minimum illumination	Colour 0.01 Lux @ F1.2 Colour 0.018 Lux @ F1.6
Infrared lighting	0 Lux / EXIR LEDs IR (30 m)
Image improvements	WDR (120dB), BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	Slot for MicroSD card, Max 128 GB
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, PSIA, CGI, ISAPI
Power supply	DC 12 V / 800 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +50° C
Dimensions	244.4 mm (D) x 105 (Ø) mm
Weight	1015 g