

DS-2CV2041G2-IDW(2.8mm)(E)

Hikvision

IP Bullet Camera Wi-Fi range

Resolution 4 Megapixel (2560x1440)

Lens 2.8 mm | Wi-Fi IEEE802.11b/g/n

IR range 30 m | Built-in microphone
and loudspeaker

MicroSD card slot up to 256 GB



Hikvision

Wi-Fi range

Bullet IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2560x1440)

2.8 mm Lens

0 Lux

EXIR IR scope 30 m

Compression H.265+ / H.265 / H.264+ / H.264

Integrated microphone

Integrated speaker

WDR (120 dB)

3D-DNR

MicroSD card slot up to 256 GB

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

WiFi IEEE802.11b/g/n

Weatherproof IP66

Specifications

Brand	HIKVISION
Range	Wi-Fi
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	20 fps (2560x1440), 25 fps (1920x1080, 1280x720)
Extra Stream rate	25 fps (1280x720, 640x480, 640x360)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 95°, V: 53°, D: 111°
Range performance	63 m (D), 25 m (O), 12 m (R), 6 m (I)
Electronic Shutter	1/3~1/100.000 s
Minimum illumination	Colour: 0.005 Lux @(F1.6, AGC ON) 0 Lux with EXIR IR range 30 m
Day/Night	Removable mechanical ICR filter
Image improvements	WDR (120 dB), BLC, 3D-DNR, Mirror
Motion Detection	Yes
Internal memory	Slot for MicroSD card up to 256 GB
Audio	Built-in microphone and speaker
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio bit rate	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)
Network interface	Ethernet 10 / 100 BaseT Wi-Fi IEEE802.11 b/g/n
WiFi frequency	2.412 GHz ~ 2.472 GHz
WiFi modulation	802.11n: BPSK, QPSK, 16QAM, and 64QAM 802.11b: DBPSK and DQPSK, CCK 802.11g: BPSK, QPSK, 16QAM, and 64QAM
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 500 mA / 6 W max.
Degree of protection	Weatherproof IP66
Material	Base: Metallic Front cover: Metal Rear cover: Plastic
Temp. operation	-30° C ~ +60° C
Dimensions	73 mm (H) x 89.1 mm (W) x 175.6 mm (D)
Base dimensions	Ø base 70 mm / Ø entre tornillos 55 mm / 3 tornillos
Weight	335 g