

HWI-D180H

IP Camera 8 Mpx Hikvision Hiwatch

1/2.8" Progressive Scan CMOS

Compression H.265+ / H.265 /

H.264+ / H.264

Lens 2.8 mm | PoE (IEEE802.3af)

IR LEDs Range 30 m

Suitable for exterior IP67



Hikvision

IP camera

1/2.8" Progressive Scan CMOS

8 Megapixel (3840x2160)

2.8 mm Lens

0 Lux

IR Range 30 m

H.265+/H.265/H.264+/H.264

Dual stream

RJ45 10/100 BaseT

3DNR, BLC, AGC, Mirror, Privacy Mask

IR Cut

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Vandal proof IK10

Specifications

Brand	Hikvision
Range	HiWatch Series
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	8 Megapixel (1920x1080)
Main Stream rate	(3840 × 2160)@12.5FPS, (2560 × 1440, 1920 × 1080, 1280 × 720)@25 FPS
Extra Stream rate	(640 × 480, 640 × 360) 25 [%VAR%] FPS
Compression	H.265+/H.264+/H.265/H.264
Bitrate	32 Kbps ~ 16 Mbps
Lens	2.8 mm (108°)
Minimum illumination	Colour 0.01 Lux @ F2.0
Infrared lighting	0 Lux / IR LEDs (30 m)
Image improvements	DWDR, BLC, 3D-NR, AGC, Motion detection
Day / Night	Removable mechanical ICR filter
Alarms	No
Audio	No
Network interface	Ethernet 10/100 BaseT
Internal memory	No
Remote access	Web Browser, Smartphone App IVMS 4500 and PC Software IVMS 4200
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 500 mA / PoE (IEEE802.3af)
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	82.4 mm (D) x 111 (Ø) mm
Weight	410 g