

DAHUA-2977

DH-HAC-HDW2501TMQP-A-0280B-S2



DAHUA 4 IN 1 DOME 5MP WITH SMART IR 60M



- Dahua 4-in-1 PRO series fixed dome with 60m Smart IR for outdoor use
- 5MP 1/2.7" CMOS
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switchable by DIP switch
- Fixed 2.8 mm (111°) optics
- 0.001 lux
- ICR filter
- OSD, AWB, AGC, BLC, HLC, HLC-Pro, WDR 120dB, 2D/3D-NR, mirror mode, privacy masks
- Built-in microphone
- IP67
- 3AXIS
- 12V DC



Reference / Model

DAHUA-2977 / DH-HAC-HDW2501TMQP-A-0280B-S2

5-megapixel 1/2.7" CMOS sensor

Digital resolution: 5MP (2880x1620), 4MP (2560x1440), 1080P (1920x1080), 960H (960x576)

Frames per second: 25 fps @5MP (CVI), 25 fps @4MP (CVI/TVI/AHD), 25 fps @1080P (CVI)

4-in-1 output switchable via DIP switch

Day/Night mode with removable mechanical filter (ICR)

0.001 lux F1.6 (colour) / 0 Lux IR On

Smart IR: 2 LEDs, up to 60 metres

2.8 mm fixed optics

Viewing angle: 111°(H), 58°(V), 132°(D)

OSD via coax (5MP video up to 700 metres).

Picture modes: BLC, HLC, HLC-Pro, WDR 120dB, 2D/3D-NR, Mirror.

Automatic and manual white balance

Automatic and manual gain control

DAHUA 4 IN 1 DOME 5MP WITH SMART IR 60M

Reference / Model	DAHUA-2977 / DH-HAC-HDW2501TMQP-A-0280B-S2
	Supports 8-zone rectangular privacy mask
	Built-in microphone
	Power supply: 12V DC (±30%)
	Power consumption: 5.9W (max.)
	Storage temperature -40°C ~ +60°C (-40°C ~ +60°C)
	Operating temperature range -40°C ~ +60°C
	Relative humidity: <95% (non-condensing)
	Degree of protection IP67
	Metal housing
	Dimensions: Ø121.9 x 99.1 (H) mm
	Weight: 430 g
	3AXIS: 0°~360°(PAN), 0°~78°(TILT), 0°~360°(Rotation)