

NVR1104HS-W-S2-CE-IMOU

NVR1104HS-W-S2-CE-IMOU



4 Channel 1080P WiFi IMOU IP NVR

H.265+

- 4 Channel 1080P WiFi IMOU IP NVR
- H.265 + / H.265 / H.264 + / H.264
- Playback of up to 4 channels
- Recording up to 40 Mbps
- HDMI (1080P) and VGA (1080P) outputs
- 1 HDD SATA III capacity
- 1 RJ45 Fast Ethernet
- 2 USB 2.0
- 12V DC
- Desktop.



Reference / Model

NVR1104HS-W-S2-CE-IMOU / NVR1104HS-W-S2-CE-IMOU

Specs

H.265 + / H.265 / H.264 + / H.264 video encoding

4 IP camera inputs

HDMI and VGA video outputs at 1080P (1920x1080)

Two-way audio: 1 RCA input / 1 RCA output

Output division: 1, 4

Display resolution: 1080P (1920x1080), SXGA (1280x1024), 720P (1280x720), XGA (1024x768)

Recording resolution: 1080P (1920x1080), 720P (1280x720), etc.

Recording speed in wired mode: 40 Mbps

Recording speed in WiFi mode: 16 Mbps

Simultaneous 4-channel playback

Decoding capability of 1 channel 6MP at 25 ips, 2 channels 4MP at 25 ips, 4 channels 1080P at 25

ips, 8 channels 720P at 25 ips

4 Channel 1080P WiFi IMOU IP NVR

Reference / Model**NVR1104HS-W-S2-CE-IMOU / NVR1104HS-W-S2-CE-IMOU**

Storage: 1 SATA port up to 8TB (HDD not included)

RJ45 network interface (10 / 100M)

Built-in WiFi module with dual 2x2 MIMO antenna

WiFi standard IEEE802.11b / g / n, 100 meters in open field

Compatible ONVIF profiles T / S / G, SDK, CGI

IMOU App Compatible with iPhone, iPad, Android mobile devices

Connections: 2 USB 2.0

Server Access local network and Internet

Independent configurable video sensor per camera

USB ports for external devices

Software and hardware watchdog

Watermark to preserve the integrity of the videos

Possibility of limiting user access to cameras in local and / or remote mode

Area masking, video loss and camera concealment alarm

Multilanguage display menu

Remote viewing, configuration and control via TCP / IP with client program and Internet Explorer browser (also compatible with Firefox and Chrome browsers)

Sending emails with attached photograph in alarm

Send to FTP scheduled or in alarm

Possibility of sending alarm, and being connected to video surveillance receiver software

Power supply: 12V DC / 1.5A ($\leq 10W$, without discs)

Operating temperature: $-10^{\circ}C \sim +45^{\circ}C$

Relative humidity: 10% ~ 90%

Dimensions: 260.3 x 247.3 x 44.7mm (desktop)

Weight: 824g (without HDD)